



INSPIRATION CS 5.2

Compact Streaming CD-Receiver with 2 x 330 Watt

Product Information

EVOLUTION CS 5.2

Compact Streaming CD-Receiver with 2 x 330 Watt



EVOLUTION CS 5.2 in brief

- 4 line inputs, 1 phono input (MM & MC)
- 1 Pre Out, 1 Line Out
- 3 digital inputs (SPDIF, opt., synchronous USB- input)
- Pure CD drive with Slot-in, spring mounted
- Streaming Formats: MP3, WMA, AAC, OGG Vorbis, FLAC (192/32 via LAN), WAV (192/32 via LAN),
 AIFF (192/32 via LAN), ALAC (96/24 via LAN)
- Supported media server: UPnP 1.1, UPnP-AV and DLNA-compatible server,
 Microsoft Windows Media Connect Server (WMDRM 10), DLNA-compatible servers: NAS
- Web radio: vTuner Internet Radio Service, Auto network config.,
 Internet Radio Station database (automatic updates)
- Digital signal processing with 192 kHz / 24 Bit (Upsampling of all incoming digital signals into this format)
- WLAN & LAN
- FM-RDS-Tuner
- Highly efficient power amps with 330 W/Ch
- Speakers A/B switchable
- Pure Class-A headphone output with 6,3 mm banana plug
- Sleepmode: Maintains network access and enables switching the CS 2.2 on and off via the RC 9 remote control and AVM RC S App
- Tone control and parametric loudness with bypass-function
- Large blue graphic display
- Vast Menu functions (i.e. adjustable input sensitivity, individual naming of inputs etc.)
- Housing options: Aluminum silver or black, chrome front optional
- RC 9 remote control with color display and charging dock optionally available
- RC S remote control app for iOS and Android

Our most compact music system in the EVOLUTION line is our CS 5.2. It offers the large power of more than 300 Watts per channel. The CS 5.2 offers a large variety of connectivity and control functions. Every well known format is supported when music is streamed from different sources. Furthermore the CS 5.2 offers a variety of digital inputs like synchronous USB input and SPDIF in and outputs. A NAS or externa drive are supported as well as a USB jump drive (stick). An excellent phono stage is included too as well as 3 line inputs. The firmware of the streaming client is updateable and upgradeable, making the CS 5.2 future proof. This way possible future formats may be implemented as well.

With it's 330 Watt/ch strong amplifier, the CS 5.2 easily handles all speakers in the market. Cutting edge technologies are applied when it comes to digital signal processing with all digital signals being up sampled to 192kHz/24bit and a dual DAC converting to analog signal from this format. All this ensures a perfect music reproduction from every applicable source. Special focus was put on achieving the most authentic reproduction from CD. The acoustically shielded Pure CD drive is spring mounted end effectively protected from vibrations and footfall.

EVOLUTION CS 5.2

Compact Streaming CD-Receiver with 2 x 330 Watt



Like all AVM hi-fi components the CS 5.2 is carefully developed and assembled by our engineers in Malsch, Germany. Our vendors for housing and electronic parts reside all near-by. This proximity helps us to easily ensure and maintain superb quality level of the supplied parts for the AVM hi-fi components made of these.

During the manufacturing process we perform repeatedly numerous tests to insure the absolute quality of our products. When the assembling is finished and the first inspection is done all units must pass a run in test in order to prove their reliability. After that a careful final inspection follows before packing & shipping. All this ensures creating a perfect product from AVM for our customers.

>200

Technical Data EVOLUTION CS 5.2

Amplifier

Input impedance Phono 47 k Ω / 100 | SNR 96 dB(A) SNR Phono 83 dB(A)

SNR Phono 83 dB(A)
Crosstalk (Phono) 55 dB

Frequency range $$<5~{\rm Hz}->50~{\rm kHz}$$ ${\rm TM}$ 25 W/4 ${\Omega}$ \$<0,1~%

Rated power into in 4 Ω 2 x 330 Watt Rated power into 8 Ω 2 x 220 Watt

Tuner

Damping factor

Frequency range 87,5 – 108,0 MHz Tuning steps 50 kHz Sensitivity (mono / stereo) 1,5 μ V / 50 μ V TIM (mono / stereo) 73 / 68 dB(A)





EVOLUTION CS 5.2

Compact Streaming CD-Receiver with 2 x 330 Watt



CD, digital in/out

Formats CD-Audio, CD-R
Upsampling 192 kHz / 24 Bit
Frequency range <5 Hz - 20 kHz
Deemphasis yes, automatic

Digital inputs 33–192 kHz / 16–24 Bit

(S/PDIF, TOSLINK)

USB-input up to 48 kHz / 16 Bit
Digital-outputs 44,1 kHz / 16 Bit
(S/PDIF, TOSLINK) or input format

Computer Audio: Streaming, NAS and more

Streaming Formats:

MP3, WMA, AAC, OGG Vorbis, FLAC (192/32 via LAN), WAV (192/32 via LAN), AIFF (192/32 via LAN), ALAC (96/24 via LAN)

Supported media server:

UPnP 1.1, UPnP-AV und DLNA-compatible Server, Microsoft Windows Media Connect Server (WMDRM 10), DL-NA-compatible Server: NAS

Webradio:

vTuner Internet Radio Service, Auto network config., Internet Radio Station database (automatic updates)
Digital signal processing with 192 kHz / 24 Bit (all incoming digital signals are being converted to this format)
Network connection via WLAN or LAN

Miscellaneous

Power supply 230V/50Hz or 120V/60Hz

Maximum power consumption 990 W

Dimensions (B x H x T) 430 x 130 x 370 mm

Weight 12 kg