



See nothing, hear everything

Need big sound, slamming bass and audiophile bass extension, but don't want to see where it comes from? Then the new ISW-4 in-wall subwoofer is the product for you. Its two long-throw 200mm drivers allows the ISW-4 to move large volumes of air needed for high-quality low-frequency output, but is nicely hidden away inside a wall. Powered by a separate audiophile-standard 250W Class D amplifier the SA250 Mk2, the system keeps its cool even when the music movie action is whipping up a storm.

ISW-4 Technical Specifications

| | |
|----------------------------|--|
| Description | In wall subwoofer system with external rack-mount amplifier |
| Drive units | 2 x 200mm (8 in) Paper/Kevlar® cone |
| Frequency range | -6dB at 17Hz and 290Hz adjustable (EQ at A) |
| Frequency response | ±3dB 21Hz - 200Hz adjustable (EQ at A) |
| Bass extension | -6dB at 17Hz (position A) -6dB at 21Hz (position B) -6dB at 24Hz (position C) |
| Power Handling | 200W 8Ω (minimum 6.3Ω) |
| Dimensions | Height: 494mm (19.5 in) Width: 264mm (10.4 in) Depth: 99mm (3.9 in) Depth with grille: 114mm (4.5 in) |
| Cut-out size | Height: 485mm (19.9 in) Width: 255 (10 in) |
| Net weight | 6.4kg (14.1lb) |
| Finish Frame/Grille | Semi-matt white suitable for customising or pre-painting |
| Accessories | Pre-mount kit for new construction |
| Back Box | |
| Box | Height: 1406mm (55.4 in) Width: 345mm (13.6 in) Depth: 86mm (3.4 in) |
| Net Weight | 9.6kg (21.2lb) |
| Material | MDF |

Custom Installation SA250 Mk2



SA250 Mk2 Technical Specifications

| | |
|--------------------------------|--|
| Description | 250W rack-mount amplifier with built-in subwoofer equalisation |
| Amplifier inputs | <ul style="list-style-type: none">- 2x RCA Phono socket, line in- 2x RCA Phono socket, link out- 1x XLR socket, line in- 1x XLR socket, link out- 3.5mm jack - 12V trigger on/standby (overrides manual standby setting)- 3.5mm jack - 12V trigger equalisation movie/music |
| Amplifier outputs | <ul style="list-style-type: none">- 1x Neutrik® Speakon® 4-pole speaker socket- 2x pairs of Binding Posts |
| Amplifier power output | 250W |
| Input impedance | 33k Ω |
| Signal / noise | >80dB |
| Rated power consumption | 95W – 1/8 full power 30W – Idling |
| Dimensions | Height: 100mm (3.9 in) [88.5mm (3.5 in) plus feet] Width: 430mm (16.9 in) Depth: 322mm (12.7 in) Front panel Height: 2U 88.1mm/3.5 in |
| Net weight | 5.4kg (11.9 lb) |
| Finish | Black |

Bowers & Wilkins

www.bowers-wilkins.com

Kevlar is a registered trademark of DuPont.
Speakon is a registered trademark of Neutrik AG
Copyright © B&W Group Ltd. E&OE
B&W Group Ltd reserves the right to amend details of the specification without notice in line with technical developments